

Sewing Pattern — Sarafan with Shaped Relieve 5461

Recommendations on fabric: sheer flax.

You will also need: fusing; 12 buttons; piping.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Side front part – 2 pieces
2. Front part – 1 piece
3. Triangle gusset – 2 pieces
4. Back part – 2 pieces
5. Placket – 4 pieces

Fusing: placket.

INSTRUCTIONS:

1. Apply the fusing to wrong side of placket.
2. Lay placket details together and overstretch placket outer edge. Topstitch overstretching allowance on placket at 0.2 cm from seam. Neaten placket outer edge.
3. Sew the placket to front part. Topstitched placket neaten edge along seam joining the placket. Press ready placket.
4. Sew triangle gusset to front part. Neaten joining seam and press forward.
5. Neaten lower edge of front lower part. Press allowance and topstitch at 0.5 from lower edge.
6. Make buttonholes into placket. Fix front part and side front part along side seam and along front neckline edge.
7. Neaten back middle edge. Sew back middle seam and press it apart. Sew side edges of garment and neaten them. Press side seam backwards.
8. Press the piping along the center and overstretch edges of: front/back neckline, front/back armholes.

9. Sew shoulder seams and press backwards. Neaten the hem, press it under and topstitch. Sew buttons.

TECHNICAL DRAWING:

