

Sewing Pattern —Dress 5449

Recommendations on fabric: natural fabric.

You will also need: zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Front central part – 1 piece
3. Skirt back panel – 2 pieces
4. Skirt front panel – 1 piece
5. Front insert – 1 piece
6. Shoulder strap – 4 pieces
7. Bust cup – 2 pieces

INSTRUCTIONS:

1. Sew front insert to front panel. Neaten the seam and press it.
2. Sew darts into back part and front center part. Press darts towards the center.
3. Make pleats into cups. Press pleats and fix them.
4. Fold string details right sides together and overstretch strap outer edge. Topstitch neaten seam on lower string at 0.2 cm from seam and press the strap.
5. Make piping for armholes and back neckline. Fold piping along the center and press it. Sew folded a piping to back neckline edge and armhole edge of cups and back part; piping bend is on the garment at 0.75 width. Cut seam allowances to 0.5 cm width. Turn piping into wrong side of garment and topstitch it along back neckline and armhole of cups and back.
6. Sew raw edge of upper strap to cup outer edge. Fold edge of lower strap under and topstitch it along joining seam.
7. Sew skirt back panel to back part. Neaten seam and press it backwards.

8. Sew front panel to front center part. Neaten the seam and press it towards front center.
9. Neaten back middle seam.
10. Sew side edges of garment and shoulder edges of garment. Neaten side and shoulder seams. Press side and shoulder seams backwards.
11. Sew garment middle seam up to closure notch. Press the seam apart and press closure slits. Sew the zipper in.
12. Neaten the hem. Press it to wrong side and topstitch.

TECHNICAL DRAWING:

