

Sewing Pattern — Lace Trim Blouse 5424

Recommendations on fabric: lightweight linen, silk or mixed blouse fabric.

You will also need: 5 buttons, iron-on interfacing and lace 2-7 cm in width.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Collar - 2 pieces
2. Collar stand – 2 pieces
3. Sleeve - 2 pieces
4. Cuff - 2 pieces
5. Back - 2 pieces
6. Side – 2 pieces
7. Upper front – 2 pieces
8. Middle front - 2 pieces
9. Centre front –2 pieces
10. Front band –4 pieces

Interfacing: front band, top collar, cuff and collar stand.

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the front band, top collar, cuff and the collar stand.
2. Stitch the centre and the middle front pieces together. Neaten and press the seams.
3. Pleat the upper front lower edge. Stitch the upper front to the lower front; neaten the seam; press the seam allowances upwards. With right side to the wrong side, pin under front band to the front piece; stitch along the front centre edge; press the seam allowances to the front band.
4. Stitch the back centre edges; neaten and press the seam.
5. Stitch the blouse side piece to the front/back piece. Neaten the seams; press the seams towards the

front/back centre.

6. Press one long edge of the top front band under. With right sides together, stitch the top front band raw edge to the under front band raw edge. Fold the top front band to the garment right side and press.
7. Neaten the lace lower edge; press the edge under and topstitch. Pleat the lace long edge. With the lace between, topstitch the top front band to the front. Topstitch the lace upper edge to the garment 0,5 cm below the neckline.
8. Stitch the shoulder seams; neaten the seams; press the seams backwards.
9. Make up and shape the collar.
10. Stitch the collar stands together along the top/front edges, placing the collar between them.
11. Stitch the collar to the neckline; topstitch the collar around.
12. Stitch the sleeve seams.
13. Make up and shape the cuffs.
14. Stitch the cuffs to the sleeves; neaten the seams; press them upwards. Topstitch the seam allowances to the sleeves; topstitch the cuffs around.
15. Stitch the sleeves to the armholes. Neaten the seams.
16. Make buttonholes; attach buttons.
17. Neaten the blouse hem; fold the hem under and topstitch.

TECHNICAL DRAWING:

