

Sewing Pattern — Blouse 5422

Recommendations on fabric: lightweight natural fabric

You will also need: decorative cord or ribbon

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back - cut 1
2. Front – cut 1
3. Sleeve - cut 2

INSTRUCTIONS:

1. Sew back darts, serge, and press toward center.
2. Sew side and shoulder seams. Serge, and press toward back.
3. Serge neck edge, turn under, and topstitch 0.7 cm below the fold.
4. Serge or zigzag the front keyhole edge, turn under, and topstitch 0.7 cm around the fold. Thread a cord (ribbon) into the front casing.
5. Sew the sleeve seams. Serge and press seams toward back.
6. Make a gathering stitch along sleeve cap for ease. Sew the sleeves to the armholes, matching marks and adjusting ease.
7. Serge the lower edge of garment, turn onto wrong side, and topstitch.

TECHNICAL DRAWING:

