

## Sewing Pattern — Dress 5339

Recommendations on fabric: chiffon, elastic guipure

You will also need: zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm. for all seams, 2 cm. for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Centre front – 1 piece
2. Side back – 2 pieces
3. Centre back – 2 pieces
4. Side front – 2 pieces

Guipure:

1. Back sleeve – 2 pieces
2. Front sleeve – 2 pieces
4. Binding stripe - 4 cm in width.

ADVICE: to prevent seam from stiffing, stitch pieces with special (zigzag) stitch. To prevent hem from stiffing neaten it with overlocker and then stitch using double needle. Do the same for all edges must stay elastic.

The above is not for industrial manufacturing.

### **INSTRUCTIONS:**

1. Stitch the front/back curved edges. Press the front seams towards the front centre, and the back seams towards the back centre.

2. Stitch and neaten the sleeve seams.
3. Stitch and neaten the side seams. Press the side seams backwards.
4. Stitch the sleeves to the armholes.
5. Finish the neckline by applying binding stripe or ready bias binding.
6. Neaten the back centre edges. Stitch the seam up to the closure notch. Press it seam open pressing the slit. Sew the zipper in.
7. Fold the dress and sleeve hems to the wrong side and stitch in place.

**TECHNICAL DRAWING:**

