

Sewing Pattern — Trousers 5332

Recommendations on fabric: light stretch fabric – natural or mixed

You will also need: fusing, 1 zipper; 1 button.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : 1 cm for all seams, 3 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front – 2 pieces
2. Back – 2 pieces
3. Back facing – 1 folded piece
4. Front facing – 2 pieces
5. Zip guard – 1 piece

Fusing: front facing, back facing, zip guard

INSTRUCTIONS:

1. Apply fusing to the wrong side of the facings and the zip guard.
2. Stitch darts. Press them towards the center.
3. Neaten the edges and stitch the side/inside leg seams. Press them open.
4. Stitch the crotch seam up to the closure mark.
5. Press the closure fly extensions to the wrong side. Stitch the zip tape edges to the slit left edge and to the right fly extension. Fold the zip guard inside out and overstitch along two short sides. Turn it right side out. Neaten the long edge. Topstitch the left fly extension to the guard. Topstitch the slit right edge close to the fold line catching the extensions.

6. Join the front and back neck facing across the shoulder seams. Press the seams open. Neaten the raw edge. Overstitch the garment top edge with the facing. Slipstitch the ends of the facing to the zip tape. Topstitch the waistline. Press the hems under. Stitch them in place.
8. Make buttonhole in the right front edge, apply the button to the left front edge.

TECHNICAL DRAWING:

