

Sewing Pattern — Blouse 5327

Recommendations on fabric: chiffon, silk

You will also need: 1 zipper, decorative braid

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : on hem – 2 cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Lower back – 2 pieces
2. Side front – 2 pieces
3. Middle front – 2 pieces

Chiffon:

1. Upper back – 2 pieces
2. Upper front – 2 pieces
3. Sleeve – 2 pieces
4. Sleeve flounce – 2 pieces

INSTRUCTIONS:

1. Stitch and press towards the centre back the back darts.
2. Stitch the front curved edges; neaten the seams; press them towards the centre front.
3. Stitch the front central seam and neaten it. Press the seam towards the left front piece.
4. Stitch side seams of the lower pieces and neaten them. Press the seams backwards.
5. Stitch the shoulder/side seams and neaten them. Press these seams backwards.
6. Stitch flounces to the sleeves. Neaten the seams. Neaten the flounce lower edges and topstitch decorative braid.

7. Stitch the sleeve and the flounce side edges in one continuous seam. Neaten the seam. Stitch the sleeves to the armholes according to the notches.
8. Neaten the neck edges.
9. Stitch the garment upper piece to the garment lower piece. Neaten the joining seam. Topstitch decorative braid to the neckline.
10. Neaten the back central edges. Stitch them up to the notch. Press the seam open. Sew zipper in with its teeth hidden.
11. Neaten the garment hem and topstitch decorative braid.

TECHNICAL DRAWING:

