

## Sewing Pattern — Leather jacket 5318

Recommendations on fabric: artificial leather

You will also need: fusing; 4 buttons; lining

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Upper back part – 2 details
2. Center lower back part – 2 details
3. Side lower back part - 2 details
4. Inner collar - 1 detail
5. Upper collar – 1 detail
6. Side lower front part – 2 details
7. Upper front part – 2 details
8. Center lower front part - 4 details
9. Front band – 2 details
10. Upper sleeve – 2 details
11. Lower sleeve – 2 details
12. Lower sleeve facing – 2 details
13. Upper sleeve facing – 4 details
14. Pocket – 2 details

#### Lining:

1. Center back part – 1 detail
2. Side back part - 2 details
3. Side front part – 2 details
4. Center front part – 2 details
5. Upper sleeve – 2 details
6. Lower sleeve – 2 details
7. Pocket lining – 2 details

Fusing: front band, upper front part, center lower front part, inner collar; hem allowance: side lower front part, side lower back part, center low back part.

OUR ADVICE: if wished, make holes (with special tool) into front and back upper dart segments, lower front parts-lower back parts joining seams, sleeve front seams and collar-lapel joining visible seam, then pull decorative cord into.

### **INSTRUCTIONS:**

1. Strengthen the front band, upper front part, center lower front part, inner collar; hem allowance: side lower front part, side lower back part, center low back part with clue interfacing.
2. Overstitch inner collar with outer one (right sides together). Cut, then turn the collar right side out.
3. Sew inner edges of side lower front part and center lower front part. Sew inner edges of side lower back part and center lower back part. Sew vertical darts into front/back parts. Sew lower back parts to upper back part. Sew back center seam.
4. Fold the pocket with the right side of upper front part. Fold the pocket lining with the side lower front part, lining right side down. Sew them. Turn the seam over and topstitch on Hessian.
5. Sew lower front part to upper front part, with pocket entrance unstitched. Sew pocket Hessian.
6. Fold the front band with front part right sides together, then overstitch along edge line. Overstitch on the front part upwards the notch defining the end of collar sewing into. Sew front bands lower edges to front part strictly along marked hemline. Cut upper and lower seams corners. Overstitch the front band work seam allowance: at zipper area – into the front band, on lapels area – into the front part edge, on 0,2 cm width from the seam. Turn the edges into right sides, fit seams.
7. Sew shoulder and side seams.
8. Sew the inner collar to the neckline. Sew the outer collar to front bands.
9. Sew sleeve elbow seam up to the notch. Sew side sleeve facing edges up to notches. Fold sewn facings with upper sleeve right sides together, then overstitch along lower and side up to the notch. Sew sleeve upper edge and side edges with one stitch. Cut facing seams allowance and turn the facing out, trimming seams. Press facings through the pressing cloth.
10. Sew the sleeves into the armholes according to notches. Sew shoulder pads and sleeve heads.
11. Sew lining details seams, then sew sleeves into armholes, with the hole into sleeve right front seam. Press the lining. Sew the lining to front band inner edges and outer collar. Sew collar joining seam allowance near seams.
12. Sew lining sleeves to lower edge of sleeve facing. Fold the extra lining under and press. Sew the lining to fabric jacket hem. Turn the jacket right side out through the hole in the sleeve. Sew the hole in the sleeve.

13. Work buttonholes into right front part, then sew buttons to left one.

**TECHNICAL DRAWING:**

