

## Sewing Pattern — Jacket 5315

Recommendations on fabric: wool fabric suitable for coats

You will also need: fusing; 6 buttons; lining

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Center back part – 2 details
2. Side back part – 2 details
3. Back yoke – 1 detail
4. Front yoke – 2 details
5. Side front part – 2 details
6. Center front part – 2 details
7. Inner collar – 1 detail
8. Outer collar – 1 detail
9. Belt – 4 details
10. Front band – 2 details
11. Upper sleeve – 2 details
12. Lower sleeve – 2 details

#### Lining:

1. Center back part – 1 detail
2. Side back part - 2 details
3. Side font part – 2 details
4. Center front part – 2 details
6. Upper sleeve – 2 details
7. Lower sleeve – 2 details

Fusing: front band, center front part front yoke, back yoke, side back part armhole, inner collar;  
hem allowance: side back part, center back part, lower sleeve, upper sleeve

OUR ADVICE: if wished, you can insert a contrast piping into over stitching seams: collar, edge and belt, as well as into sleeve hem and garment hem seams

### **INSTRUCTIONS:**

1. Strengthen the upper center front part, center front part, front yoke, side back part armhole, inner collar; hem allowance: side back part, center back part, lower sleeve, upper sleeve.
2. Overstitch inner collar with outer one (right sides together). Cut, then turn the collar right side out.
3. Overstitch the belt along the outer contour. Cut the corners, then tuck the belt. Press belt and oversew the loop.
4. Sew and press front relieves. Make decorative snitch along front relief on 0.7 cm distance from the joining seam.
5. Sew back relieves inserting the belt between. Press the back relieves and make decorative stitch along back relief on 0.7 cm from joining seam.
6. Pin the front band and front part right sides together, then over stitch along the edge, on the front part side, up to the notch pointing the end of sewing-in the collar. Sew front bands low edges strictly along the marked line of hem turning-under. Cut upper and lower seams of the edge. Topstitch joining seam allowance into the front band, on 0.2 cm from the seam. Turn edges into right side, trim seams.
7. Sew shoulder and side seams, then press apart.
8. Sew inner collar to neckline, then sew outer one to front bands.
9. Sew sleeve elbow seam, then press. Make decorative stitch along elbow seam on 0.7 cm distance from joining seam.
10. Sew sleeve front seam, then press. Press sleeve hem into the wrong side.
11. Sew sleeves into armholes according to notches. Sew shoulder pads and sleeve heads.
12. Sew lining sleeve seams, then sew the sleeves into, with the holes into front right seam of sleeves. Sew the lining to front band and outer collar inner edges. Press collar joining seam allowances apart and fix sew near seams.
13. Sew the lining to garment and sleeves hems. Turn the garment right side out through holes in sleeves, then sew holes.
14. Work buttonholes into right front part, and sew buttons to the left one.

**TECHNICAL DRAWING:**

