

Sewing Pattern — Top 5306

Recommendations on fabric: cotton, viscose, knitted fabric.

You will also need: elastic braid

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 1 detail
2. Front part drawstring – 1 detail
3. Back part - 1 detail
4. Back part drawstring – 1 detail
5. Front stand-up collar – 1 detail
6. Back stand-up collar – 1 detail
7. Back stand-up collar drawstring – 1 detail
8. Front stand-up collar drawstring – 1 detail
9. Tie – 4 details

OUR ADVICE: To make the fabric along stitched seams stretch, sew details with narrow zigzag or with special stretchable stitches. To make the hem stretch, oversew hem allowance with special oversewstitches (overlock), and then sew it using double needle. This is also attachable to other edges that should stay elastic.

These recommendations are not for industry.

INSTRUCTIONS:

1. Oversew front/back parts armhole allowances, fold them under and topstitch.

2. Tuck tie ends. Fold ties along the center and stitch on 0.7 cm from the fold center. Turn tie into right side, then press. Sew ends.
3. Oversee shoulder edges. Sew shoulder seams. Topstitch shoulder seams along both sides from joining seam on 1 cm width. Tuck ties into allowances.
4. Overstitch front stand-up collar with front drawstring. Overstitch back stand-up collar with back drawstring.
5. Sew stand-ups collars side edges to drawstrings, with unstitched spaces in drawstring left side seam, for elastic braid. Turn the collar into right side and press.
6. Make stitches for elastic braid in accordance with marking. Sew the collar to neckline.
7. Pull elastic braid into and fix its ends.
8. Sew front part drawstring to front part hem. Sew back part drawstring to back part hem.
9. Sew garment side seams as well as front/back parts facing side seams, with unsewn space in the drawstring left side seam, for elastic braid.
10. Make stitches for elastic braid in accordance with marking.
11. Pull elastic braid into and fix its ends.

TECHNICAL DRAWING:

