

## Sewing Pattern — Blouse 5305

Recommendations on fabric: soft silk and viscose

You will also need: clue interfacing; 3 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part - 2 details
  2. Back part - 1 detail
  3. Front band - 2 details
  4. Sleeve - 2 details
  5. Collar - 2 details
  6. Lapels – 2 details
- Cut 2 fabric ties of 3 cm width.

Clue interfacing: front band, outer collar, lapel.

### **INSTRUCTIONS:**

1. Strengthen the front band, outer collar and the lapel with clue interfacing.
2. Sew bust darts into front part and waist vertical ones into front/back parts.
3. Sew shoulder seams.
4. Sew side seams.

5. Sew inner lapel to inner collar.
6. Sew upper lapel to outer collar.
7. Overstitch inner collar and lapel with outer collar and lapel, then turn into right side and press.
8. Tack inner edge of front bands.
9. Overstitch right front part with front band, inserting the lapel and collar. Make a notch into outer collar and bend it. Sew inner collar to back neckline, make one more notch into outer collar and overstitch left front part with front band.
10. Turn front bands into wrong side. Oversew and press edges. Fold the outer collar open edge under and topstitch along the inner collar joining seam. Sew front band into shoulder seams with 1 cm width stitch.
11. Sew sleeve seams.
12. Press sleeve hem into wrong side and topstitch along drawstring marking.
13. Tuck tie ends. Fold ties along the center and stitch on 0.7 cm from the fold center. Turn tie into right side, then press. Sew ends. Pull ties into drawstring loop.
14. Sew sleeves into armholes, fitting along caps.
15. Oversew garment hem, then fold under and topstitch along the edge.
16. Work button holes into right part. Sew buttons to left one.

**TECHNICAL DRAWING:**

