

Sewing Pattern — Blouse 5300

Recommendations on fabric: chiffon (natural silk, polyester)

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 1 detail
2. Back part - 1 detail
3. Sleeve - 2 details
4. Wide ruffle - 2 details
5. Narrow ruffle – 2 details

Cut pipings of 0.5 cm width by diagonal.

INSTRUCTIONS:

1. Sew vertical darts into front and back parts.
2. Sew wide and narrow ruffles to sleeve hem.
3. Sew sleeve seams.
4. Sew side seams.

5. Sew sleeves into arm holes.
6. Fold piping for figure neckline along the center and press. Sew folded pipings to edges of figure neckline; piping bent should be on the garment on 0.75 cm width. Cut seam allowances to 0.5 cm width. Turn pipings into wrong side, then topstitch the blouse along figure neckline.
7. Fold under and topstitch front/back neckline edges, with drawstring loop unstitched.
8. Prepare the string and pull it into neckline loop.
9. Press sleeves and blouse hems to the wrong side and topstitch.

TECHNICAL DRAWING:

