

## Sewing Pattern — Blouse 5299

Recommendations on fabric: linen, cotton and mixed fabric.

You will also need: clue interfacing, 3 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part - 2 details
2. Back part - 1 detail
3. Front band - 2 details
4. Sleeve - 2 details
5. Collar - 2 details

Clue interfacing: outer collar.

### **INSTRUCTIONS:**

1. Strengthen the front band and outer collar with clue interfacing.
2. Sew vertical darts into front and back parts.
3. Sew shoulder seams.
4. Sew side seams.
5. Prepare loops and sew them to front part edge.
6. Oversew front bands inner edges. Overstitch the front part with front band.

7. Overstitch inner collar with outer one, then turn out and press.
8. Turn front bands into wrong side. Oversew and press edges. Sew inner collar to the neckline, fold the outer collar open edge under and topstitch along the inner collar joining seam. Sew front band into shoulder seams with 1 cm width stitch.
9. Sew sleeve seams.
10. Sew sleeves into arm holes, fitting caps.
11. Oversew sleeve and garment hem allowances, then press into wrong side and topstitch along the edge.
12. Sew buttons to the left front part.

**TECHNICAL DRAWING:**

