

Sewing Pattern — Blouse 5298

Recommendations on fabric: soft cotton or combined fabric.

You will also need: clue interfacing

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 2 details
2. Back part - 1 detail
3. Front band - 2 details
4. Sleeve - 2 details
5. Cuff - 2 details
6. Collar – 2 details
7. Stand-up collar – 2 details

Clue interfacing: front band, outer collar, cuff, stand-up collar.

INSTRUCTIONS:

1. Strengthen the front band, outer collar, cuffs and outer stand-up collar with clue interfacing.
2. Sew waist darts into back part.
3. Oversew inner edge of the front band. Overstitch the front part with front bands up to the notch, then turn faint bands into wrong side and press.
4. Make gathering along the front part center seam and sew.
5. Sew shoulder seams.

6. Sew side seams.
7. Overstitch inner collar with outer one. Turn the collar right side out.
8. Sew stand-ups, with collar between them.
9. Sew inner stand-up (with the collar) to the neckline, fold the outer stand-up open edge under and topstitch along the inner stand-up joining seam. Make decorative topstitch along the collar. Topstitch the edge. Sew front bands on shoulder seams with stitch of 1 cm width.
10. Sew sleeve seams.
11. Sew sleeves into arm hole, fitting along caps.
12. Fold cuffs right sides together. Sew short ends into ring. Make a notch into allowance (near split), with slit in the seam center. Fold cuffs right sides together, stitch edges.
13. Sew cuffs to the sleeve hem and oversew cuff upper edge with the sleeve.
14. Topstitch the cuff-on-sleeve joining seam and make decorative seam along cuff bottom and slit sides.
15. Press the hem into wrong side and topstitch.

TECHNICAL DRAWING:

