

## Sewing Pattern — Jacket 5289

Recommendations on fabric: lace knitted fabric, mixed fabric (for working).

You will also need: clue interfacing; 6 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part - 2 details
2. Back part - 1 detail
3. Front part facing - 2 details
4. Sleeve - 2 details
5. Cuff - 2 details
6. Back neckline facing – 2 details

Clue interfacing: front part facing, cuff, back neckline facing.

**OUR ADVICE:** To make the fabric along stitched seams stretch, sew details with narrow zigzag or with special stretchable stitches. To make the hem stretch, oversew hem allowance with special oversewstitches (overlock), and then sew it using double needle. This is also attachable to other edges that should stay elastic.

These recommendations are not for industry.

### **INSTRUCTIONS:**

1. Strengthen the front part facing, cuffs and back neckline facing with clue interfacing.
2. Stitch back neckline facings to shoulder edges of front part facings.
3. Oversew inner edge of front part facing and back neckline facing.
4. Sew shoulder seams, inserting selvedge.

5. Sew front part facing and back neckline facing to edge. Overstitch front/back part necklines with facing. Turn front part facing and back neckline facing into right side. Topstitch back neckline and front part facings.
6. Sew side seams.
7. Sew sleeve seams.
8. Fold cuffs right sides together. Sew short ends into ring. Make a notch into allowance (near split), with slit in the seam center. Fold cuffs right sides together, stitch edges.
9. Stitch cuffs to sleeve lower edge and oversew upper edge of the cuffs, with the sleeve.
10. Topstitch cuff-to-sleeve joining seam, then make decorative stitch along lower part of the cuff and along slits edge.
11. Sew sleeves into armhole, fitting along caps.
12. Press hem allowance into wrong side and topstitch.
13. Work button holes into right front part and sew buttons to left one.

**TECHNICAL DRAWING:**

