

Sewing Pattern — Blouse 5286

Recommendations on fabric: cotton stretch fabric.

You will also need: clue interfacing; 7 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 2 details
2. Back part – 1 detail
3. Collar – 2 details
4. Stand-up collar – 2 details
5. Sleeve - 2 details
6. Cuff – 2 details

Clue interfacing: panel, upper (outer) collar, stand-up collar, cuff.

INSTRUCTIONS:

1. Strengthen the планку, outer collar, stand-up collar and cuffs with clue interfacing.
2. Sew darts into front part. Sew waist darts into back part.
3. Sew shoulder seams.
4. Oversew sleeve edges separately p to notch marking.
5. Sew sleeves into armhole, fitting them around the cap.
6. Sew sleeve seams and side seams with single stitch.
7. Oversew inner edge of each placket.

8. Overstitch inner collar with outer one. Turn the collar right side out.
9. Sew stand-ups, with the collar between them.
10. Sew inner stand-up (with the collar) to the neckline, fold the outer stand-up open edge under and topstitch along the seam of inner stand-up. Make decorative topstitch along the collar.
11. Overstitch side edges of cuffs and turn them right side out.
12. Sew outer one-piece cuffs to the lower edge of the sleeve. Topstitch inner one-piece cuffs on.
13. Make decorative stitch along side and lower sides of cuffs.
14. Press under and topstitch the garment hem.
15. Make button holes into right (overlap) part and sew buttons to left (underlap) one.

TECHNICAL DRAWING:

