

Sewing Pattern — Jacket 5279

Recommendations on fabric: artificial/natural leather or suede.

You will also need: clue facing; 1 button.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part yoke - 2 details
2. Front part – 2 details
3. Front part insert – 2 details
4. Lower back part – 2 details
5. Back part yoke - 1 detail
6. Back part – 1 detail
7. Back part insert – 1 detail
8. Lower back part – 1 detail
9. Front band - 2 details
10. Cuff – 2 details
11. Sleeve - 2 details
12. Stand-up collar – 2 details

Clue interfacing: front band, stand-up collar.

INSTRUCTIONS:

1. Strengthen the front band and stand-up collar with clue interfacing.
2. Sew darts into front/back parts.
3. Topstitch the yoke on the front part with decorative stitches.
4. Topstitch the front part insert on the front part with decorative stitches.
5. Topstitch the front part insert on the lower front part with decorative stitches.

6. Topstitch the yoke on the back part with decorative stitches.
7. Topstitch the back part insert on the front part with decorative stitches.
8. Topstitch the back part insert on the lower back part with decorative stitches.
9. Sew shoulder seams.
10. Sew side seams.
11. Face upper (outer) stand-up collar with lower (inner) one.
12. Sew the stand-up collar into collar hole. Topstitch upper (outer) stand-up collar into topstitching seam of lower (inner) one.
13. Sew the cuff to lower edge of the sleeve.
14. Sew seams by hand.
15. Prepare the string loop.
16. Sew the loop to right front part.
17. Face front edges with front bands.
18. Sew sleeves, fitting them under sleeve caps.
19. Sew buttons on the left front par.

If wished, you can make decorative stitches along the relief seams, edges and darts.

TECHNICAL DRAWING:

