

Sewing Pattern — Jacket 5276

Recommendations on fabric: whipcord.

You will also need: lining, warmer, fusing, 1 separable zipper (depending on front part's length), 2 zippers (depending on pocket's length).

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

SEAM ALLOWANCE: 1 cm for all seams, 3.5 cm for pieces of upper part.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part – 2 pieces
2. Center back part – 1 piece
3. Side front part – 2 pieces
4. Side back part – 2 pieces
5. Sleeve – 2 pieces
6. Outer collar – 1 piece
7. Inner collar – 1 piece
8. Front band – 2 pieces
9. Large sacking – 2 pieces
10. Off-set welt – 2 pieces
11. Placket for zipper – 1 piece

Lining:

12. Front part – 2 pieces
13. Back part – 1 piece
14. Sleeve – 2 pieces
15. Small sacking – 2 pieces

Warmer:

Topstitch the warmer to wrong side of back/front parts, sleeves, placket and outer/inner collars according to contour.

INSTRUCTIONS:

1. Quilt side front/side back part according to marked lines.
2. Apply the fusing to wrong side of the welt, press the welt along the center. Lay the reinforcement stripe under pocket place. Mark a line on the welt determining ready welt's height. Lay the welt on right side of front part coinciding pocket marking and the line on the welt. Welt's outer side must coincide with front part's right side. Stitch the welt. Cut pocket entrance between marking lines making diagonal slashes towards corners of pocket marking. Turn the welt wrong side out. Press seam allowances apart. Lay the zipper under pocket entrance. Stitch the zipper to front part on right side, 0.1 cm from pocket entrance. Stitch small sacking to zipper's lower braid and fold it downwards. Stitch large sacking to zipper's upper braid. Sacking edges must enter the seam joining the zipper and reach the hem.
4. Stitch side parts to back/front parts. Stitch shoulder/side edges. Stitch sleeve seams. Stitch sleeves into armholes. Stitch around the placket for zipper and topstitch it. Overstitch the collar, turn it right side out and topstitch along collar fall. Stitch the collar into neckline.
5. Stitch front band to front part's lining making a pleat into lining. Stitch lining details together, leave technological hole into a sleeve's seam.
6. Topstitch zipper's left part on the placket. Lay zipper's part on edging right sides together (teeth are outwards edging). Overstitch edgings inserting the zipper into placket (placket is on left front part). Turn the garment right side out.
7. Stitch the lining to garment/sleeve hems. Sew technological hole.
8. Topstitch jacket's edging ad hem.
9. Press ready jacket.

TECHNICAL DRAWING:

