

## Sewing Pattern — Pants 5256

Recommendations on fabric: cotton elastic or jersey material

You will also need: contrast coloured fabric for trimming.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



**ADVICE:** to prevent seam from stiffing, sew details with special (zigzag) stitch. To prevent hem from stiffing overcast it with overlocker and then stitch using double needle. Do the same for all edges must stay elastic.

The above is not for industrial manufacturing.

### **CUTTING:**

#### Fabric:

1. Front - 1 folded piece
2. Back - 1 folded piece
3. Crotch gusset – 2 pieces.

#### Trimming:

4. Waistband – 1 piece
5. Leg opening facing – 2 pieces

### **INSTRUCTIONS:**

1. Pin the crotch gussets right side to right side sandwiching the back piece between them and stitch. Stitch the front piece to the upper crotch gusset right sides inside. Stitch the under crotch gusset to the front piece by hands.
2. Stitch the leg opening facing side edges ; stitch them to the leg openings. Turn the facings above the edges to the wrong side of the pants; fold the facing's lower edges under and topstitch them on the right side of the garment through the previously made seam.
3. Stitch the waistband side edges together. Stitch the waistband to the pants top edge. Turn the waistband around the edge to the wrong side of the pants; fold the raw edge under and topstitch it working on the right side through the previously made seam.

### **TECHNICAL DRAWING:**

