

Sewing Pattern — Set/Pants 5253

Recommendations on fabric: light silk or cotton.

You will also need: embroidered cambric; elastic tape 2cm in width; lace tape 1cm. in width.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front – 2 pieces
2. Back – 2 pieces
3. Ruffle – 2 pieces

INSTRUCTIONS:

1. Sew the side/inside leg seams. Press them open.
2. With right sides together place one half of the shorts inside the other half and stitch the crotch seam leaving a slit for the waist elastic above the waist fashion line.
3. Fold the waist self facing inside and press it. Fold the facing raw edge under and stitch it to the garment 0,1cm above this edge. Make decorative stitches according to the marks. Cut pieces of elastic to fit the waist, plus 2,5 cm. Thread the elastic through the casings. Overlap and stitch the elastic ends.
4. Stitch the ruffles side edges. Gather them and stitch to the bottom edges of drawers. Neaten the lower edges of the ruffles and fold them to the wrong side. Tack the ruffles to the garment. Topstitch the lace tape to the ruffle lower edges.

TECHNICAL DRAWING:

