

Fleece Sweatshirt - Sewing Pattern #2221

Recommendations on fabric: fleece, footer or natural/mixed thick knit fabric of small stretchiness. For decoration – knit fabric of high stretchiness in a matching color.

You will also need: zipper.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Front – cut 1 on fold
2. Back – cut 1 on fold
3. Front yoke – cut 2
4. Sleeve – cut 2

Main fabric 1:

1. Hem facing - cut 1 on fold

- 2. Cuff – cut 2
- 3. Stand collar – cut 2

INSTRUCTIONS:

1. Pin front yoke to front along the princess seams and sew up to the beginning of the lower edge of yoke. Clip into the corner of seam allowance on front and serge.
2. Sew shoulder seams. Serge seams and press towards back.
3. Sew outer stand collar into neckline, slightly stretching it stand collar. Press the seam allowance at stand collar. Sew in zipper. Serge lower edge of inner stand collar. Pin inner stand collar, right side down, onto the outer stand collar and sew upper edge. Fold away stand collar onto wrong side and press. Stitch in the ditch the lower edge of the inner collar into the seam. Slipstitch the center edge of inner stand collar to the zipper tape. Sew a decorative stitch along the zipper teeth at 0.5 cm.
4. Close the zipper. Sew the lower edge of the front yoke to front. Serge and press towards bottom. Sew a decorative stitch around all edges yokes at 0.5 cm from seam.
5. Sew sleeves into armholes, matching notches, serge and press. Sew sleeve seams and continue sewing side seams, serge and press.
6. Sew cuff into a ring. Press the seam allowances apart. Fold cuff in half lengthwise and press. Sew the cuff to the sleeve, slightly stretching the cuff. Serge.
7. Sew lower facing into a ring. Press the seam allowances apart. Fold facing in half lengthwise and press. Sew the facing to the hem, slightly stretching the facing. Serge.

TECHNICAL DRAWING:

