

Hood Scarf - Sewing Pattern #2377

Recommendations on fabric: natural/mixed knit fabric of medium stretchiness.

Seam allowances: all seams 1 cm.

Note on seam allowances:


- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Hood - cut 4

INSTRUCTIONS:

1. Pin pieces together pairwise right sides together and sew center edge of hood. Press the seam apart.
2. Pin inner side to outer side right sides together and sew along the outer edge and the tie edges, leaving an opening at the back neckline for turning.
3. Clip into seam allowances on curves, turn right side out and press.
4. Sew the opening closed.

TECHNICAL DRAWING:

