

Turtleneck With Decorative Closure - Sewing Pattern #4737

Recommendations on fabric: natural/mixed knit fabrics of small/medium stretchiness.

You will also need: knit bias tape; 5 buttons.

Seam allowances: all seams 1.0 cm. Seam allowance for hem of garment - 2.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back – cut 1 on fold

2. Front – cut 1 on fold
3. Front yoke – cut 2
4. Sleeve – cut 2
5. Cuff – cut 2
6. Stand collar – cut 1

INSTRUCTIONS:

1. Sew darts on front. Trim bulk with serger and press towards bottom.
2. Sew front yokes to front, press towards top and serge. Pin bias tape onto seam and topstitch.
3. Sew shoulder seams, press towards the back and serge.
4. Stand collar pin together in half lengthwise right sides together and sew short sides. Turn stand collar right side out, straighten, press. Make buttonholes.
5. Pin left stand collar onto right stand collar, baste together. Sew the stand collar into neckline, serge and press.
6. Sew sleeves into armholes matching notches, serge and press. Sew side seams processing the sleeve seam at the same time, press towards the back and serge.
7. Fold the cuffs into a ring right sides together and sew, press the seam apart. Cuffs turn right side out, fold in half and press. Sew a gathering stitch along lower edge of sleeve and gather fullness. Sew cuffs to sleeves, press seam allowances towards sleeve, serge.
8. Serge lower edge. Fold inside the seam allowance and topstitch.
9. Sew on buttons onto stand collar and the seam of the left yoke.

TECHNICAL DRAWING:

