

## Jacket With Knit Sleeves - Sewing Pattern #4798

Recommendations on fabric: quilted fabrics with polyester padding, suitable for outdoor jackets; knit fabric of same color.

You will also need: lining; separating zipper; two of the zipper for pockets.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment - 3 cm. Seam allowance on lower edge of sleeve - 3 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

### Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 - 0.8 cm.



## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold

2. Front - cut 2
3. Back neck facing - cut 1
4. Center front facing - cut 2
5. Front placket - cut 1
6. Pocket facing - cut 4
7. Underlay piece - cut 2

Knit fabric:

1. Sleeve - cut 2
2. Collar -cut 1

Lining:

1. Back - cut 1 on fold
2. Front - cut 2
3. Small pocket bag - cut 2
4. Large pocket bag - cut 2

Attention! Lining is cut using pattern blocks for self fabric except for the width of center front facing and back neckline facing.

## **INSTRUCTIONS:**

1. Mark the position of pocket on front. Fold pocket facings in half wrong sides together and press. Mark an additional line on facing parallel to the fold for stitching it to garment. Sew facings to front. Finish stitching at the guidance lines that you marked near pockets. Check your work on the wrong side (stitch lines should be parallel). Slash pocket opening. Snip diagonally toward end of stitching at 1-1.5 cm from end of pocket opening. Turn the facings onto wrong side through the resulting opening, straighten the edges in such a way that the pressed folded edges of facings meet each other. Fix corners of pockets in place by stitching a double stitch line from the wrong sides at the corners. Pin right side of pocket bags to wrong side of zipper tape and sew. Pin zipper under the edge of pocket opening. Sew in zipper, folding lining away. Sew edges of lining.
2. Sew shoulder seams of jacket, press the seam apart.
3. Serge lower edge of sleeve, press onto wrong side and topstitch. Sew sleeve to jacket, press towards self garment.
4. Sew side edges of jacket and press apart, sewing the sleeve edges at the same time..
5. Sew the outer collar into neckline. Clip into seam allowances and press apart.
6. Sew shoulder seams of central front facings and facings, press the seam apart. Sew inner edge of collar into neckline. Clip into seam allowances and press apart.

7. Fold front placket in half lengthwise right sides together and sew corners. Turn right side out and press. Sew decorative stitches along outer fold, along upper and lower edge. Topstitch left half of zipper onto placket, matching the edge of zipper tape with the raw edge of placket.
8. Place center front facing onto front right sides together and sew along the center front edge, inserting zipper, sewing the collar at the same time. Start and stop stitching exactly at the marked hem line.
9. Sew side and shoulder seams on lining, leaving an opening in left side seam.
10. Baste seam allowances along collar seam together. Sew lining to the central front facings and to facing. Turn garment right side out. Sew armhole in two steps: back armhole from shoulder seam to side seam, and front armhole from shoulder seam to side seam through the opening in side seam. Sew lower edge of lining to hem of garment. Sew the opening closed.

## **TECHNICAL DRAWING:**

