

## Knit Pullover With Shawl Collar And Welted Pockets - Sewing Pattern #4956

Recommendations on fabric: natural/mixed stable knit fabric with medium stretchiness and heavier weight.

You will also need: 3 buttons; knit fusible interfacing.

Seam allowances: seam allowance along hem of garment and hem of sleeve - 2 cm, other seams 1 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Front - cut 1
2. Back - cut 1 on fold
3. Collar - cut 4
4. Sleeve - cut 2
5. Pocket welt and pocket bags

Fusible interfacing:

1. Collar - cut 2
2. Pocket welt

## **INSTRUCTIONS:**

1. Mark the position of pocket. Press welt in half lengthwise wrong sides together. Topstitch small pocket bag onto inner side of welt. Sew welt to front along lower marked line of pocket. Sew large pocket bag to front along upper marked line of pocket. Stop stitching near short marking lines of the pocket. Slash through pocket opening. Snip diagonally toward end of stitching at 1-1.5 cm from end of pocket opening. Turn welt and large pocket bag onto wrong side through the resulting opening. Sew a double back stitch lines near corners to fix ends of pockets. Sew together edges of pocket bags.

2. Cut (or take ready) bias tape, its width should equal 2.5 cm and its length should equal 13 cm for loop buttonholes. Fold tape in half lengthwise right sides together and stitch at 0.3 cm from fold. Cut away seam allowances close to seam, turn tape right side out and straighten the rolled piece. Cut into three parts. Adjust length of the loop.

3. Apply fusible interfacing to collars. Sew collars along center seam, by two, press the seam apart. Pin together collar right sides together and sew along collar fall, inserting loop buttonholes on the right according to markings. Turn collar right side out, press. Pin right collar onto left collar and baste together along lower edge.

4. Sew a gathering stitch along upper edge of center front and gather fullness. Sew collar to front, serge and press.

5. Sew shoulder seams, serge and press.

6. Sew in the collar into the back neckline, slashing corners, serge and press.

7. Sew sleeves into armholes, matching notches, serge and press. Sew sleeve seams and continue sewing side seams, serge and press.

8. Serge the lower edge of garment and the lower edge of sleeve, fold onto wrong side, press and topstitch.

9. Sew on buttons according to markings. Slipstitch left part of collar into the seam, from the wrong side.

## **TECHNICAL DRAWING:**

