

Leather Jacket - Sewing Pattern #4973

Recommendations on fabric: eco leather or natural leather.

You will also need: lining; separating zipper.

Seam allowances: all seams 1 cm. Seam allowance along hem of garment and hem of sleeve - 3 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Center upper back - cut 2
2. Center lower back - cut 2
3. Side upper back - cut 2
4. Side lower back - cut 2
5. Center upper front - cut 2
6. Center lower front - cut 2
7. Side upper front - cut 2

8. Side lower front – cut 2
9. Yoke — cut 2
10. Stand collar – cut 2
11. Upper sleeve 1 – cut 2
12. Sleeve inset — cut 2
13. Upper sleeve 2 – cut 2
14. Lower sleeve 1 – cut 2
15. Lower sleeve 2 — cut 2
16. Back neck facing – cut 1
17. Center front facing – cut 2

Lining:

1. Center back – cut 2
2. Side back – cut 2
3. Front – cut 2
4. Upper sleeve – cut 2
5. Lower sleeve – cut 2

INSTRUCTIONS:

1. Sew upper side backs to upper center back. Sew lower side backs to lower center back, press towards center and topstitch at 0.2 cm from seam. Sew center seams of upper backs and lower backs, press the seam apart and topstitch at 0.2 cm from seam. Sew upper back to lower back, press towards top and topstitch at 0.2 cm from seam.
2. Sew princess seams on upper and lower fronts (= sew side fronts to center fronts), press towards center and topstitch at 0.2 cm from seam. Sew upper front to lower front, press towards top and topstitch at 0.2 cm from seam.
3. Sew yoke to back, press seam towards yoke and topstitch at 0.2 cm from seam. Sew yoke to front, press seam towards yoke and topstitch at 0.2 cm from seam.
4. Sew side seams, press the seam apart.
5. Sew sleeve inset to Upper Sleeve 1, press seam allowances towards inset and topstitch at 0.2 cm from seam. Sew Upper Sleeve 2 to sleeve inset, press seam allowances towards inset and topstitch at 0.2 cm from seam. Sew Lower Sleeve 1 to Lower Sleeve 2, press towards top and topstitch at 0.2 cm from seam. Sew elbow seam on the sleeve, seam allowance press towards upper sleeve part and topstitch at 0.2 cm from seam. Sew front sleeve seam. Sew sleeves into armholes.
6. Sew zipper to center front edges (zipper blade should be faced away from center edge).
7. Sew outer stand collar into neckline of Shell, clip seam allowances and press apart.

8. Sew shoulder seams of central front facings and facings, press the seam apart. Sew inner stand collar into neckline, clip seam allowances and press apart. Pin center front facing onto front, right sides together, and sew lower front corner, center front edge and stand collar. Clip into curves, trim away corners, turn right side out and press. Baste together seam allowances of inner and outer stand collars together.
9. Sew the pieces from lining, leaving an opening in left side seam. Sew pykava. Sew lining to center front facings, to facing and to lower edge. Turn the garment right side out through the opening. Sew lining to hem of sleeve through the opening, press seam. Sew the opening closed.
10. Sew a decorative stitch around all edges stand collars. Sew an additional decorative stitch along center front edge at 0.5 cm from zipper.

TECHNICAL DRAWING:

