

## Skirt With Wrap - Sewing Pattern #S3057

Recommendations on fabric: natural/mixed fabrics suitable for skirts.

Seam allowances: back center seam on back yoke and back waistband 5/8 inch to allow for zipper installation, hem of skirt and side of wrap edges - 1 inch, all other seams - 3/8 inch.

Ease: ease around waist around 5/8 inch, ease around hip around 1.5 inch.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Self

- (A) Front Left Skirt - cut 1
- (B) Front Right Skirt - cut 1
- (C) Front Right Yoke - cut 1
- (D) Front Left Yoke - cut 1
- (E) Back Skirt - cut 1 +1
- (F) Back Yoke - cut 1 +1
- (G) Back Waistband and Facing - cut 2 +2
- (H) Front Waistband and Facing - cut 2 on fold

Interfacing

- (G) Back Waistband and Facing - cut 1 +1
- (H) Front Waistband and Facing - cut 1 on fold

## **INSTRUCTIONS:**

1. Apply fusible interfacing to waistband facings.
2. Serge sides of wrap on Left Skirt and Right Skirt. Turn under, press and topstitch.
3. Pin Left Skirt onto Right Skirt as seen from the right side (wrong side of Left Skirt Lies on top of the right side of the Right Skirt. Base together along upper edge, matching inner upper corner of Right Skirt to center front on Left Skirt and notches. The resulting piece is referred to as Bottom Skirt in the Future.
4. Pin Left Yoke to upper edge of Bottom Skirt from center front to side seam, matching notches. Sew, serge and press towards top.
5. Pin Right Yoke to Left Yoke, matching notches and center front. Sew, serge and press towards top. The resulting piece is referred to as Front Skirt in the future.
6. Sew Back Yokes to Back Skirts, serge and press towards yokes. The resulting pieces are referred to as Back Skirts in the future.
7. Sew side seams on Back and Front Skirts. Serge and press towards back.
8. Sew side seams on front and back waistbands. Pin waistband onto right side of the skirt, right sides together, and sew. Grade seam and press towards waistband.
9. Serge center back edges separately. Sew center back seam on lower back skirts from yoke to bottom. Press seam apart, pressing the slit for zipper at the same time. Sew in zipper into center back edge of back yokes and facings.
10. Serge lower edge of waistband facings. Pin waistband facings to waistband, right sides together and sew around waist. Trim corners, turn right side out, straighten and press. Turn open lower edge under and press. Turn seam allowances near zipper under and press. Stitch in the ditch from the right side. Slip stitch seam

allowances to zipper tape.

11. Serge hem of skirt, turn under and press. Topstitch from the right side.

**TECHNICAL DRAWING:**